



Description	Distance	Details	Actual
a Between fenders	1277 mm : 50 9/32"	Measured in front area of flange inner edges	
b Between headlight compartments	776 mm : 30 9/16"	Measured at outer edges of weatherstrip seat flanges	
c Width of front luggage compartment	1380 mm : 54 11/32"	Horizontal distance to outer edge of lid weatherstrip seat	
d Length of front body assembly	1074 mm : 42 9/32"	Through vehicle center, from forward edge of body to inner flange of lid weatherstrip seat	
e Diagonally in front luggage compartment	1742 mm : 67 7/8"	Measured between forward edge of fender and outer corner edge of lid weatherstrip seat	
f Between roll bar and windshield flange	638 mm : 25 1/8"		
g Windshield flange height	788 mm : 31 1/32"	Measured between lower edge of windshield flange and upper edge of flange and door rocker panel	
h Between hinge and door lock pillars	1039 mm : 40 29/32"	Measured between bulge for door contact switch and depression for door lock plate	
i Between hinge pillars	1503 mm : 59 3/16"	Horizontal distance between hole centers on left and right sides	
k Diagonally across windshield frame	1373 mm : 54 1/16"	Measured at upper edge of windshield frame	
l Vertical windshield opening	689 mm : 27 1/8"	Measured in upper part of windshield frame in center of vehicle	
m Windshield frame width	1711 mm : 46 3/32"	Horizontal distance between inner left and right roof edges	
n Diagonal distance between rollbar and lock plate	1433 mm : 56 13/32"	Measured from corner of roll bar to top of inner hole of door lock plate on opposite side	
o Diagonal distance across rear window	1280 mm : 50 13/32"	Measured between corners of window seating surface	
p Vertical opening in rear window frame	243 mm : 9 9/16"	Measured through vehicle center between upper and lower edges of window seating surface	
q Length of rear body assembly	778 mm : 30 5/8"	Distance between flange inner edge of rear panel and vertical part of rear floor panel through center of vehicle	
r Width of opening for rear luggage compartment lid	1359 mm : 53 1/2"	Distance between left and right fender flange. Dimensions are constant through the compartment area to tail light assemblies	
s Diagonal distance across rear luggage compartment	1588 mm : 62 17/32"	Measured between inner corners of the lid weatherstrip seat	
t Diagonal distance across passenger compartment	1642 mm : 64 21/32"	Measured between corner of longitudinal member inner wall and crease in transverse member at wheel housing	
u Passenger compartment width	1228 mm : 48 11/32"	Measured between inner walls of longitudinal members; dimension is constant across entire passenger compartment	
v Passenger compartment width	717 mm : 28 7/32"	Distance between front left and right longitudinal member	
w Body height to windshield flange	578 mm : 22 3/4"	Measured at distance A = 400 mm from firewall in center of vehicle	
x Diagonal distance across roof opening	1997 mm : 52 5/8"	Measured between outer corner of roll bar and inner edge of roof on opposite side	
y Diagonal distance across passenger compartment	1976 mm : 77 25/32"	Measured at distance A = 400 mm of roll bar and outer edge of lower hole for hinge	